

Job Name:

System Reference:

Date:

460V OUTDOOR VRF HEAT PUMP SYSTEM



UNIT OPTION

Standard Model.....PUHY-EP72YNU-A1

ACCESSORIES

- Big Foot Stand.....for details see Big Foot Stands submittals
- Header Kit.....for details see Pipe Accessories Submittal
- Joint Kit.....for details see Pipe Accessories Submittal
- Low Ambient Kit.....for details see Low Ambient Kit Submittal
- Panel Heater Kit.....for details see Panel Heater Kit Submittal
- Snow/Hail Guards Kit.....for details see Snow/Hail Guards Kit Submittal

Specifications		System	
Unit Type		PUHY-EP72YNU-A1	
Cooling Capacity (Nominal)		BTU/H	72,000
Heating Capacity (Nominal)		BTU/H	80,000
Guaranteed Operating Range	Cooling	°F [°C]	23~126 [-5.0~52.0]
	Heating	°F [°C]	-13~60 [-25.0~15.5]
Extended Operating Range	Heating	°F [°C]	-27.4~60 [-33.0~15.5]
External Dimensions (H x W x D)		In. [mm]	71-5/8 x 36-1/4 x 29-3/16 [1,818 x 920 x 740]
Net Weight		Lbs. [kg]	545 [247]
External Finish			Pre-coated galvanized steel sheet (+powder coating for -BS type) [MUNSELL 3Y 7.8/1.1 or similar]
Electrical Power Requirements	Voltage, Phase, Hertz, Power Tolerance		460V, 3-phase, 60 Hz, ±10%
Minimum Circuit Ampacity		A	14.0
Maximum Overcurrent Protection		A	20
Recommended Fuse Size		A	15
Recommended Minimum Wire Size		AWG [mm]	14 [2.1]
SCCR		kA	5
Refrigerant Piping Diameter	Liquid (High Pressure)	In. [mm]	3/8 [9.52] Brazed
	Gas (Low Pressure)	In. [mm]	7/8 [22.2] Brazed
Max. Total Refrigerant Line Length		Ft.	3,280 [1,000]
Max. Refrigerant Line Length (Between ODU & IDU)		Ft.	541 [165]
Max. Control Wiring Length		Ft.	1,640 [500]
Indoor Unit Connectable	Total Capacity		50.0~130.0% of outdoor unit capacity
	Model/Quantity		P04~P72/1.0~18.0
Sound Pressure Levels		dB(A)	55.0/57.0
Sound Power Levels		dB(A)	74.5/76.0
FAN ⁴	Type x Quantity		Propeller fan x 1
	Fan Motor Output	kW	0.92
	Airflow Rate	CFM	6,000
	External Static Pressure	In. WG	Selectable; 0.00, 0.12, 0.24, 0.32, In. WG; factory set to 0 In. WG
Compressor Operating Range			15.0% to 100.0%
Compressor	Type x Quantity		Inverter scroll hermetic compressor x 1
Refrigerant	Type x Original Charge		R410A x 14.0 lbs + 5.0 oz [6.5 kg]
Protection Devices	High Pressure Protection		High pressure sensor, High pressure switch at 4.15 MPa (601 psi)
	Inverter Circuit (Comp./Fan)		Over-current protection
AHRI Ratings (Ducted/Non-ducted)	EER		12.2/13.7
	IEER		22.2/27.1
	COP		4.05/4.57

NOTES:

Nominal cooling conditions (Test conditions are based on AHRI 1230-2023)
 Indoor: 80°F D.B./67°F W.B. (26.7°C D.B./19.4°C W.B.), Outdoor: 95°F D.B. (35°C D.B.)
 Nominal heating conditions (Test conditions are based on AHRI 1230-2023)
 Indoor: 70°F D.B. (21.1°C D.B.), Outdoor: 47°F D.B./43°F W.B. (8.3°C D.B./6.1°C W.B.)

¹Harsh weather environments may demand performance enhancing equipment. Ask your Mitsubishi Electric representative for more details about your region

²For details on extended cooling operation range down to -10° F DB, see Low Ambient Kit Submittal

³When applying product below -4°F, consult your design engineer for cold climate application best practices, including the use of a backup source for heating

⁴Unit will continue to operate in extended operating range, but capacity is not guaranteed

OUTDOOR UNIT: PUHY-EP72YNU-A1 – DIMENSIONS

PUHY-EP72T/YNU-A1


Unit: mm (in.)

Connecting pipe specifications

Material	Refrigerant pipe *1		Service valve	
	Liquid	Gas	Liquid	Gas
(E)P72	φ3.52(3/8)	φ2.2(7/8)	Brazed	φ3.52(3/8)
				φ2.2(7/8)

*1 Connect the refrigerant pipe to the service valve according to the Installation Manual.

NO.	Usage	Specifications
①	For pipes	Front through hole: 148(5-7/8) X 84(3-5/16) Knockout hole
②		Bottom through hole: 140(5-11/16) X 34(3-3/4) Knockout hole
③		Front through hole: φ62(2-1/2) or φ 34(51-3/8) Knockout hole
④		Front through hole: φ43(1-3/4) or φ22(7/8) Knockout hole
⑤		Bottom through hole: φ62(2-1/2) Knockout hole
⑥		Bottom through hole: φ52(2-1/16) Knockout hole
⑦	For transmission cables	Front through hole: φ34(1-3/8) Knockout hole
⑧		Bottom through hole: φ34(1-3/8) Knockout hole



Note 1. Please refer to (2/2) for information regarding necessary splicing around the unit and foundation work.
 2. At brazing of pipes, wrap the refrigerant service valve with wet cloth and keep the temperature of refrigerant service valve under 120°C(248°F).

1340 Satellite Boulevard Suwanee, GA 30024
 Toll Free: 800-433-4822 www.mehvac.com

